

Power Divider

GHPD12S-2.5-5G

Applications

- . **Wireless Communications**
- . **SATCOM**
- . **Test and Measurement**
- . **Military Communications**
- . **Commercial Communications**

Description

GHPD12S-2.5-5G 12 way SMA power divider (also known as a SMA coaxial power splitter) is rated for a minimum frequency of 2.5 GHz and a maximum frequency of 5 GHz. This Goghel 12 port SMA power divider / coaxial splitter has a 50 Ohm impedance and a maximum input power of 18 Watts(cw). Our SMA coaxial RF splitter / divider has a female SMA input and 12 female SMA output ports.

This 12 way SMA RF power divider from Goghel is a reactive design and has a maximum insertion loss of 0. The maximum input VSWR of this SMA reactive splitter / divider is 1.50:1 (1.4:1) and the minimum isolation is 18 dB.

Goghel offers power dividers and combiners that are highly reliable with exceptional specifications offering broadband frequency ranges, high isolation, low insertion loss, low VSWR, low and high power solutions and can utilize different material construction such as stripline, microstrip, and lumped element technology to support various requirements and applications.

Electrical Specifications

Model	GHPD12S-2.5-5G
NO.of Ways	12
Frequency Range (GHz)	2.5 ~ 5
Insertion Loss (dB)	$\leq 2(1.2)$
Isolation(dB)	≥ 18
VSWR	$\leq 1.50:1(1.40:1)$
Amplitude Balance(dB)	$\leq \pm 0.6$
Phase Balance($^{\circ}$)	$\leq \pm 8(6)$
Power Handling(Watt)	Forward Power: ≤ 20 (CW)
Operating Temperature($^{\circ}\text{C}$)	-25 ~ +65
Impedance	50 Ω
Port Connectors	SMA–Female
Surface Color	Black Paint (Options)
Outline Drawing	As Below

