

Power Divider

GHPD2S-4-18G

Applications

- . **Wireless Communications**
- . **SATCOM**
- . **Test and Measurement**
- . **Military Communications**
- . **Commercial Communications**

Description

GHPD2S-4-18G 2 way SMA power divider (also known as a SMA coaxial power splitter) is rated for a minimum frequency of 4 GHz and a maximum frequency of 18 GHz. This Goghel 2 port SMA power divider / coaxial splitter has a 50 Ohm impedance and a maximum input power of 10 Watts(cw). Our SMA coaxial RF splitter / divider has a female SMA type input and 2 female SMA output ports.

This 2 way SMA RF power divider from Goghel is a reactive design and has a maximum insertion loss of 0. The maximum input VSWR of this SMA reactive splitter / divider is 1.50:1 and the minimum isolation is 17 dB.

Goghel offers power dividers and combiners that are highly reliable with exceptional specifications offering broadband frequency ranges, high isolation, low insertion loss, low VSWR, low and high power solutions and can utilize different material construction such as stripline, microstrip, and lumped element technology to support various requirements and applications.

Electrical Specifications

Model	GHPD2S-4-18G
NO.of Ways	2
Frequency Range (GHz)	4 ~ 18
Insertion Loss (dB)	≤ 0.8
Isolation(dB)	≥ 17
VSWR	$\leq 1.50:1$
Amplitude UnBalance(dB)	$\leq \pm 0.25$
Phase Unbalance($^{\circ}$)	$\leq \pm 5$
Power Handling(Watt)	Forward Power: ≤ 10 (CW VSWR=1:1) 4W Max into output loads with VSWR=2.0:1 Max
Operating Temperature($^{\circ}\text{C}$)	-25 ~ +65
Impedance	50 Ω
Port Connectors	SMA-Female
Surface Color	Black Paint (Options)
Outline Drawing	As Below

